

#### **Methanol**

# 14262-6X1L

Revision Date 05/10/2024 Print Date 12/19/2024 Version 1.3

#### **SECTION 1. IDENTIFICATION**

Product name Methanol

Number 000000020240

Product Use Description Laboratory chemicals

Manufacturer or supplier's

details

Honeywell International Inc.

115 Tabor Road

Morris Plains, NJ 07950-2546

For more information call : 1-800-368-0050

+1-231-726-3171(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or

+1-703-527-3887

(24 hours/day, 7 days/week)

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

: liquid Form

Color : colourless

Odor : characteristic

#### Classification of the substance or mixture

Classification of the substance : Flammable liquids, Category 2

or mixture

Specific target organ toxicity - single exposure, Category 1,

Eyes, Nervous system, Systemic toxicity

#### GHS Label elements, including precautionary statements



#### **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Symbol(s)





Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Causes damage to organs.

Precautionary statements : **Prevention:** 

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face

protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF exposed: Call a POISON CENTER or doctor/ physician. In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Hazards not otherwise

classified

: Repeated or prolonged exposure may irritate eyes, skin and

respiratory system.



#### **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

#### Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : CH4O

Chemical nature : Substance

Chemical name	CAS-No.	Concentration	
Methanol	67-56-1	<=100.00 %	

#### **SECTION 4. FIRST AID MEASURES**

General advice : First aider needs to protect himself. Move out of dangerous

area. Take off all contaminated clothing immediately. Show this

safety data sheet to the doctor in attendance.

Inhalation : Call a physician immediately. Remove to fresh air. If not

breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is

present.

Skin contact : After contact with skin, wash immediately with plenty of water.

Call a physician immediately.

Eye contact : Rinse thoroughly with plenty of water, also under the eyelids.

Protect unharmed eye. Call a physician immediately.

Ingestion : Immediately give large quantities of water to drink. Do NOT

induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately.

Notes to physician

Most important

: No information available.

symptoms/effects, acute and



#### **Methanol**

14262-6X1L

Revision Date 05/10/2024 Print Date 12/19/2024 Version 1.3

delayed

Indication of immediate medical attention and special treatment needed, if

necessary

Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry powder

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during

firefighting

: Flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2) Formaldehyde

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

Further information : Use water spray to cool unopened containers.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Remove all sources of ignition.

Wear personal protective equipment. Unprotected persons

must be kept away.

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

Page 4 / 16



#### **Methanol**

#### 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods and materials for containment and cleaning

up

Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

#### Handling

Precautions for safe

handling

: Exhaust ventilation at the object is necessary.

Use explosion-proof equipment.

Wear suitable protective clothing and gloves.

Advice on protection against :

fire and explosion

The heavy vapours can overcome a considerable distance up to

the source of ignition.

Use only in explosion-proof areas.

Keep product and empty container away from heat and sources

of ignition.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

#### Storage

Conditions for safe storage,

including any incompatibilities

Keep only in the original container, tightly closed, in a well

ventilated place.

Store at room temperature.

(Ambient temperature: > 0 < 35°C)

Protect from atmospheric moisture and water.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Page 5 / 16



# **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.

Do not swallow.

Do not breathe vapours or spray mist.

Engineering measures : Use with local exhaust ventilation.

Electrical equipment should be protected to the appropriate

standard.

Eye protection : Safety goggles

Hand protection : Impervious butyl rubber gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Recommended Filter type:

Organic gas and low boiling vapour type

Hygiene measures : When using do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the

product.

Keep working clothes separately.

Do not swallow.

Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

#### **Exposure Guidelines**

Exposure Galaciii	103				
Components	CAS-No.	Value	Control parameters	Upda te	Basis
Methanol	67-56-1	STEL: Short term exposure limit	325 mg/m3 (250 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended



# Methanol

on 1.3		Revision Date	05/10/2024		Print Date 12/19/2
Methanol	67-56-1	PEL: Permissi ble exposure limit	260 mg/m3 (200 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Methanol	67-56-1	STEL : Short term exposure limit	325 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	TWA : Time weighted average	260 mg/m3 (200 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Methanol	67-56-1	TWA : Time weighted average	(200 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended
Methanol	67-56-1	REL: Recomm ended exposure limit (REL):	260 mg/m3 (200 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Methanol	67-56-1	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended



# Methanol

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Methanol	67-56-1	SKIN_FI NAL: Skin designati on (Final Rule Limit applies):	Can be absorbed through the skin.	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Methanol	67-56-1	SKIN_DE S : Skin designati on:	Danger of cutaneous absorption	01 2020	ACGIH:US. ACGIH Threshold Limit Values, as amended
Methanol	67-56-1	STEL : Short term exposure limit	(250 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values, as amended

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Color : colourless

Odor : characteristic

Odor threshold : Note: No data available

pH : Note: Not applicable

Melting point/range : -98 °C

Boiling point/boiling range : 64 - 65 °C at 1,013 hPa

Flash point : 52 °F (11 °C)

Method: DIN 51755

Evaporation rate : Note: No data available

Page 8 / 16



#### **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Flammability : Not applicable (solid, gas)

Lower explosion limit : 5.5 %(V)

Upper explosion limit : 50 %(V)

Vapor pressure : 128 hPa

at 20 °C(68 °F) 532 hPa at 50 °C(122 °F)

Vapor density : Note: No data available

Density : 0.79 g/cm3 at 20 °C

Water solubility : Note: completely miscible

Partition coefficient:

n-octanol/water

: log Pow: -0.71

Ignition temperature : 455 °C

Method: DIN 51794

Auto-ignition temperature : Note: not auto-flammable

Decomposition temperature : Note: At normal pressure may be distilled without

decomposition.

Viscosity, dynamic : ca. 0.55 mPa.s at 25 °C

Viscosity, kinematic : Note: No data available

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : 32.04 g/mol

Page 9 / 16



# **Methanol**

14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Global warming potential : 2.8

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions
Conditions to avoid

: Hazardous polymerisation does not occur.

: Heat, flames and sparks. Keep away from direct sunlight.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Formaldehyde

**SECTION 11. TOXICOLOGICAL INFORMATION** 

Acute oral toxicity : LD50: 5,630 mg/kg

Species: Rat

Acute inhalation toxicity : LC50: > 80 mg/l

Exposure time: 4 h Species: Rat

Acute dermal toxicity : LD50: > 10,000 mg/kg

Species: Rabbit

Page 10 / 16



#### **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Skin irritation : Species: Rabbit

Result: No skin irritation

Eye irritation : Species: Rabbit

Result: No eye irritation

Sensitisation : Note: No data available

Repeated dose toxicity : Species: Rat

Application Route: Inhalation

Note: Developmental Toxicity NOAEL (maternal toxicity) 10,000 ppm NOAEL (developmental toxicity) 5,000 ppm

Skeletal and visceral malformations.

Genotoxicity in vitro : Note: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Note: In vivo tests did not show mutagenic effects

Further information : Note: When swallowed, there is a danger of blindness. Solvent

vapours have a narcotic effect if inhaled in high concentrations. Causes damage to organs (eyes, nervous system, systemic

toxicity)

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity effects**

Toxicity to fish : LC50: 15,400 mg/l

Exposure time: 96 h

Species: Lepomis macrochirus (Bluegill sunfish)

Toxicity to daphnia and other : EC50: > 10,000 mg/l

aquatic invertebrates

EC50: > 10,000 mg/l Exposure time: 48 h

Species: Daphnia magna (Water flea)

Page 11 / 16



#### **Methanol**

#### 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Toxicity to algae : Note: No data available

Toxicity to bacteria : EC50: ca. 71,000 mg/l

Species: Bacteria

Elimination information (persistence and degradability)

Bioaccumulation : Note: Bioaccumulation is unlikely.

Mobility : Note: No data available

Biodegradability : Result: Readily biodegradable.

Value: 99 %

Method: OECD Test Guideline 301D

Further information on ecology

Biochemical Oxygen Demand : Value: 1,120 mg/g

(BOD)

Chemical Oxygen Demand : Value: 1,500 mg/g

(COD)

Additional ecological

information

, 55

: Do not flush into surface water or sanitary sewer system.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

**DOT** UN/ID No. : UN 1230

Proper shipping name : METHANOL

Class 3
Packing group II
Hazard Labels 3

**IATA** UN/ID No. : UN 1230

Page 12 / 16



#### **Methanol**

#### 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Description of the goods : METHANOL

Class : 3
Packaging group : II
Hazard Labels : 3 (6.1)
Packing instruction (cargo : 364

aircraft)

Packing instruction : 352

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

**IMDG** UN/ID No. : UN 1230

Description of the goods : METHANOL

Class : 3
Packaging group : II
Hazard Labels : 3 (6.1)
EmS Number : F-E, S-D
Marine pollutant : no

IMDG Code segregation group according chapter 3.1.4.4: NONE,

#### **SECTION 15. REGULATORY INFORMATION**

#### **Inventories**

USA. List of Active : On TSCA Inventory

Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as

amended

Australia. Inventory of : On the inventory, or in compliance with the inventory

Industrial Chemicals (AIIC),

as amended

Canada. Domestic : All components of this product are on the Canadian DSL

Substances List (DSL), as

amended

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals : 0

Inventory (KEČI)

: On the inventory, or in compliance with the inventory

Philippines. Inventory of : On the inventory, or in compliance with the inventory

Page 13 / 16



# **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

Chemicals and Chemical Substances (PICCS)

Chemical Substances

(IECSC)

China. Inventory of Existing : On the inventory, or in compliance with the inventory

New Zealand. Inventory of

Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

Taiwan Chemical

Substance Inventory (TCSI)

: On the inventory, or in compliance with the inventory

#### **National regulatory information**

US. EPA CERCLA

Hazardous Substances (40

CFR 302)

: The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the

Reportable Quantity (RQ):

Reportable quantity: 5000 lbs

Methanol 67-56-1

**SARA 302 Components** 

: No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

**SARA 313 Components** 

: The following components are subject to reporting levels

established by SARA Title III, Section 313:

: Methanol 67-56-1

SARA 311/312 Hazards

: Fire Hazard

Acute Health Hazard Chronic Health Hazard

**CERCLA Reportable** 

Quantity

: 5000 lbs



#### **Methanol**

# 14262-6X1L

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

California Prop. 65

WARNING: This product can expose you to chemicals, listed below, known to the State of California to cause birth defects or other reproductive harm. For more information go to

www.P65Warnings.ca.gov.

Methanol 67-56-1

Massachusetts RTK : Methanol 67-56-1

New Jersey RTK : Methanol 67-56-1

Pennsylvania RTK : Methanol 67-56-1

Global warming potential : 2.8

#### **SECTION 16. OTHER INFORMATION**

	HMIS III	NFPA
Health hazard	: 2*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

#### \* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

#### **Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous



# Methanol

1	42	62	-63	<b>X</b> 1	
	-	uz	-01	^	

Version 1.3 Revision Date 05/10/2024 Print Date 12/19/2024

versions.

Previous Issue Date: 10/09/2023

Prepared by Honeywell Energy and Sustainabilty Solutions Product Stewardship Group Product

Stewardship Group

Page 1	6/	1	C
--------	----	---	---