Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

SECTION 1. IDENTIFICATION

Product name : Acetone

Number : 000000011300

Product Use Description : Solvent

Manufacturer or supplier's

details

Honeywell International Inc.

115 Tabor Road

Morris Plains, NJ 07950-2546

For more information call : 1-800-368-0050

+1-231-726-3171(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or

+1-703-527-3887

:

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid, clear

Color : colourless

Odor : sweet mint-like

Classification of the substance or mixture

Classification of the substance : Flammable liquids, Category 2

or mixture

Flammable liquids, Category 2
Eye irritation, Category 2A

Specific target organ toxicity - single exposure, Category 3,

Central nervous system

GHS Label elements, including precautionary statements

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Symbol(s)





Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Call a POISON CENTER/ doctor if you feel unwell. If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Acetone NF, 2-Propanone, Diethyl Ketone, Dimethylketal,

Dimethylformaldehyde, Pyroacetic acid. Pyroacetic ether

Formula : C3H6O

Chemical nature : Substance

	Chemical name	CAS-No.	Concentration
Acetone		67-64-1	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician if

irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician.

Ingestion : Do not induce vomiting without medical advice. If a person

vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious

person. Call a physician.

Page 3 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Notes to physician

Most important

: No information available.

symptoms/effects, acute and

delayed

Indication of immediate

medical attention and

special treatment needed, if

necessary

: Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Dry chemical

Foam

Carbon dioxide (CO2)

Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during

firefighting

: Extremely flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

for firefighters

Special protective equipment : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Wear personal protective equipment. Unprotected persons

must be kept away.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Page 4 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods and materials for containment and cleaning

up

Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

: Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Advice on protection against :

fire and explosion

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

No sparking tools should be used.

No smoking.

Storage

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Conditions for safe storage,

including any incompatibilities

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

Page 6 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Hygiene measures When using, do not eat, drink or smoke.

Wash hands and face before breaks and immediately after

handling the product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Exposure Guidelines					
Components	CAS-No.	Value	Control parameters	Upda te	Basis
Acetone	67-64-1	STEL: Short term exposure limit	2,400 mg/m3 (1,000 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Acetone	67-64-1	PEL: Permissi ble exposure limit	2,400 mg/m3 (1,000 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Acetone	67-64-1	TWA : Time weighted average	1,800 mg/m3 (750 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Acetone	67-64-1	TWA : Time weighted average	(250 ppm)	03 2015	ACGIH:US. ACGIH Threshold Limit Values, as amended
Acetone	67-64-1	REL: Recomm ended exposure limit (REL):	590 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Acetone	67-64-1	STEL:	(500 ppm)	03	ACGIH:US. ACGIH
Accione	0, 04 1		(300 ppiii)		
		Short		2015	Threshold Limit
		term			Values, as amended
		exposure			
		limit			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid, clear

Color : colourless

Odor : sweet mint-like

Odor threshold : Note: No data available

pH : Note: Not applicable

Melting point/range : -94.8 °C

Boiling point/boiling range : 56 °C

Flash point : -4 °F (-20 °C)

Method: closed cup

Evaporation rate : Note: No data available

Lower explosion limit : 2.5 %(V)

Upper explosion limit : 13 %(V)

Vapor pressure : 240 hPa

at 20 °C(68 °F)

Vapor density : 2.0 Note: (Air = 1.0)

Page 8 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Density : 0.79 g/cm3 at 20 °C

Water solubility : Note: completely soluble

Partition coefficient:

n-octanol/water

: Pow: 0.58 log Pow: -0.24

Ignition temperature : 465 °C

Decomposition temperature : Note: No data available

Viscosity, dynamic : Note: No data available

Viscosity, kinematic : Note: No data available

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : 58.08 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Heat, flames and sparks.

Keep away from direct sunlight.

Incompatible materials : Acids

Aldehydes Alkalis Amines Ammonia

Page 9 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Oxidizing agents Reducing agents Chlorine compounds

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50: 5,800 mg/kg

Species: Rat

Acute inhalation toxicity : LC50: 32000 ppm

Exposure time: 4 h Species: Rat

Acute dermal toxicity : LD50: > 7,426 mg/kg

Species: Guinea pig

Skin irritation : Species: Rabbit

Result: Mild skin irritation Exposure time: 24 h

Eye irritation : Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Repeated dose toxicity : Species: Rat

NOEL: 19000 ppm

Note: 8-Week Inhalation Toxicity Study 5 days/week for 8 weeks Slightly reduced weight gain compared to controls

: Species: Rat

NOEL: 100 mg/kg/d

Page 10 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Note: 90-Day Oral Toxicity Study increased liver and kidney

weights

: Species: Rat

Lowest observed effect level: 500 mg/kg/d

Note: 90-Day Oral Toxicity Study increased liver and kidney

weights

Genotoxicity in vitro : Result: negative

Method: Mutagenicity (Salmonella typhimurium - reverse

mutation assay)

: Result: negative

Method: Chromosome aberration test in vitro

: Result: negative Method: Point mutation Note: Mouse lymphoma cells

: Result: negative

Method: DNA cell-binding Assay

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : LC50: 5,540 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

: LC50: 8,300 mg/l

Exposure time: 96 h

Species: Lepomis macrochirus (Bluegill sunfish)

Toxicity to daphnia and other

aquatic invertebrates

: LC50: 10 mg/l

Exposure time: 24 h

Species: Daphnia magna (Water flea)

Toxicity to algae : EC50: 3,020 mg/l

Page 11 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Exposure time: 14 d

Species: Chlorella pyrenoidosa (algae)

Toxicity to bacteria : LC50: > 1,000 mg/l

Species: Bacteria

Elimination information (persistence and degradability)

Biodegradability : anaerobic

Result: Readily biodegradable

Value: 78 %

Method: OECD 301 D

Further information on ecology

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1090

Proper shipping name : ACETONE

Class 3
Packing group II
Hazard Labels 3

IATA UN/ID No. : UN 1090

Description of the goods : ACETONE

Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

Page 12 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

IMDG UN/ID No. : UN 1090

Description of the goods : ACETONE

Class : 3 : 11 Packaging group Hazard Labels : 3

: F-E, S-D EmS Number Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

USA. List of Active

Substances on the Toxic Substances Control Act (TSCA) Chemical

Substances Inventory, as

amended

Australia. Inventory of

Industrial Chemicals (AIIC),

as amended

: On the inventory, or in compliance with the inventory

Canada. Domestic

Substances List (DSL), as

amended

: All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

: On TSCA Inventory

Korea. Existing Chemicals

Inventory (KECI)

: On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical

Substances (PICCS)

: On the inventory, or in compliance with the inventory

Chemical Substances

(IECSC)

China. Inventory of Existing : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as

published by ERMA New

: On the inventory, or in compliance with the inventory

Page 13 / 15

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

Zealand

Taiwan Chemical

Substance Inventory (TCSI)

: On the inventory, or in compliance with the inventory

National regulatory information

US. Drug Enforcement Administration (DEA) Listed

Precursor and Essential Chemicals (21 CFR 1310)

: On the United States Drug Enforcement Authority (DEA) List of

Precursors and Essential Chemicals

- :

: Acetone 67-64-1

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

CERCLA Reportable

Quantity

: 5000 lbs

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Acetone 67-64-1

New Jersey RTK : Acetone 67-64-1

Pennsylvania RTK : Acetone 67-64-1

Honeywell

Acetone

LP010-4

Version 1.8 Revision Date 03/15/2024 Print Date 11/19/2024

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	1
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

^{* -} Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 05/07/2019

Prepared by Honeywell Energy and Sustainabilty Solutions Product Stewardship Group Product

Stewardship Group